OSCAR LG

DESCRIZIONE: Proiettore in alluminio orientabile, da binario e superficie. Sorgente LED con driver incorporato, disponibile dimmerabile DALI, food.

DESCRIPTION: Adjustable aluminum spotlight. Track or surface. LED source with driver on board. Available dimmable DALI, food.

DIMENSIONI:
DIMENSIONS:
mm



FINITURE: Alluminio naturale, nero opaco, bianco opaco.
FINISHES: Natural aluminum, matt black, matt white.

ACCESSORI:
ACCESSORIES: DEF, GRF, KBM, KPP/S, PZ-LG, XTSAF, XTSAF-PG

Caratteristiche tecniche/Technical data

Code	LG2 - LG3 - LG4
Flux lm	2300 / 3300 / 4000
Watt	17/24/28
Kelvin	3000K/4000K
Beam	16° - 38° - 50°
Int. protection	IP20 - class I
Energy efficiency	A++
CRI	92

Accessori/Accessories

DEF
Deflettore in alluminio naturale, nero, bianco.
Barn doors, natural aluminum, black, white.

KBM
Base fissaggio parete zincata, nero, bianco.
Wall base in galvanized iron, black, white.

PZ
Pinza PVC per proiettori.
Professional spotlight clamp.

GRF
Griglia in acciaio zincato.
Steel protection grid.

KPP/S-KMP/S-PPK/S
Pantografo.
Alluminio, nero, bianco.
Pantograph.
Aluminum, black, white.

TRIPOD
Tripod, sostegno da terra per proiettori, faro non incluso.
Tripod support for spotlight.
Spotlight not included.

XTSAF
Attacco binario.
Track adapter.

XTSAF - PG/PM/PP
Pantografo con attacco binario.
Pantograph with adapter for track.